

Photovoltaic and Solar Thermal Modeling with the EnergyPlus Calculation Engine

Preprint

B.T. Griffith and P.G. Ellis

*To be presented at the World Renewable Energy Congress VIII and Expo
Denver, Colorado
August 29–September 3, 2004*



NREL

National Renewable Energy Laboratory
1617 Cole Boulevard, Golden, Colorado 80401-3393
303-275-3000 • www.nrel.gov

Operated for the U.S. Department of Energy
Office of Energy Efficiency and Renewable Energy
by Midwest Research Institute • Battelle

Contract No. DE-AC36-99-GO10337

NOTICE

The submitted manuscript has been offered by an employee of the Midwest Research Institute (MRI), a contractor of the US Government under Contract No. DE-AC36-99GO10337. Accordingly, the US Government and MRI retain a nonexclusive royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for US Government purposes.

This report was prepared as an account of work sponsored by an agency of the United States government. Neither the United States government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States government or any agency thereof.

Available electronically at <http://www.osti.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors, in paper, from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831-0062
phone: 865.576.8401
fax: 865.576.5728
email: <mailto:reports@adonis.osti.gov>

Available for sale to the public, in paper, from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22161
phone: 800.553.6847
fax: 703.605.6900
email: orders@ntis.fedworld.gov
online ordering: <http://www.ntis.gov/ordering.htm>



Photovoltaic and Solar Thermal Modeling with the EnergyPlus Calculation Engine

B. T. Griffith and P. G. Ellis

Center for Buildings and Thermal Systems

National Renewable Energy Laboratory

Introduction

EnergyPlus is a whole-building energy analysis software program being developed by the U.S. Department of Energy. Based on the Heat Balance Model, the program performs a comprehensive simulation of the building envelope, fenestration, HVAC systems, and daylighting (Crawley et al. 2001). EnergyPlus is a fully geometric model intended for annual energy simulations and runs at timesteps from 10-minutes to one hour.

EnergyPlus was recently expanded with the addition of new active solar components for simulating photovoltaic (PV) and solar thermal hot-water systems (e.g., solar collectors). The active solar models were integrated into the program because low- or zero-energy buildings often utilize renewable energy resources to accomplish their energy-saving goals. This paper provides an overview of the new models for PV and solar collectors in EnergyPlus and describes some preliminary efforts to validate the implementations.

Solar and Shading Calculations

PV and solar thermal components take advantage of the detailed solar and shading calculations already implemented in EnergyPlus for the thermal modeling of building surfaces (UIUC & LBNL 2004). The geometry of a standard EnergyPlus surface object determines the area, location, tilt, and azimuth of the PV array or solar collector. Each surface object is defined by a set of up to four vertex coordinates in three-dimensional space.

Incident solar radiation on the PV or collector surface is calculated using the same algorithms used for all exterior surfaces and is calculated separately for beam, sky, and ground reflected components based on surface geometry. Reflections from nearby surfaces, such as other building façades, are also optionally taken into account. Sky radiation is calculated using the Perez anisotropic sky model (Perez et al. 1990). The shading algorithm automatically accounts for self-shading geometries and is based on coordinate transformation methods similar to Groth and Lokmanhekim (1969) and the shadow overlap method of Walton (1983). Shading of the PV array or solar collector by other surfaces, such as nearby buildings or trees, is also taken into account based on the detailed geometry. Likewise, the PV or collector surface can shade other surfaces, for example, reducing the incident radiation on the roof beneath it. Partial transmission through a semi-transparent shading surface is also calculated. Incident solar radiation data are obtained from hourly weather data (such as TMY2) and made available for sub-hourly timesteps by carefully distributing and interpolating data between the hours.

Photovoltaics

EnergyPlus offers three different models for predicting the electricity produced by photovoltaics. Energy production is based on the assumption that the quasi-steady power prediction is constant and continuous over the simulation timestep. The choice of *simple*, *equivalent one-diode* or *Sandia model* determines the mathematical algorithm used to calculate solar electric energy production. The simple model allows the user to input

arbitrary conversion efficiencies. The other two models use empirical relationships to more accurately predict PV operating performance based on conditions such as incident radiation and cell temperature.

Simple Model

The simple model is intended to give the user complete control over the PV performance. Instead of modeling efficiencies based on operating conditions, the simple model uses arbitrary, user-defined conversion efficiencies for the PV array and inverter. Especially useful for early phase design analysis, this model allows the user to perform an initial simulation to estimate annual production and peak power without having to specify (or determine) the detailed performance coefficients of a particular PV module. A building integrated mode is available to account for electrical energy removed from building surfaces.

Equivalent One-Diode Model

The equivalent one-diode model is a four-parameter empirical model to predict the electrical performance of crystalline (both mono and poly) PV modules. The model was developed largely by Townsend (1989) and is detailed by Duffie and Beckman (1991). Originally developed as a component for the TRNSYS program by Eckstein (1990), it was ported to EnergyPlus in Version 1.1.1 by Bradley (UIUC & LBNL 2004). The model simulates a PV module with an equivalent circuit consisting of a direct-current source, diode, and one or two resistors. The strength of the current source is dependent on incident solar radiation. The current-voltage characteristics of the diode depend on the temperature of the solar cells: the hotter the module, the lower its electrical output. The model determines current as a function of load voltage. Other outputs include current and voltage at the maximum power point along the current-voltage curve, open-circuit voltage, short-circuit current as well as electrical load met and unmet. The EnergyPlus implementation employs the Eckstein model for crystalline PV modules, using it whenever the short-circuit current-voltage slope is set to zero or a positive value as modified by Ulleberg (2000). The model automatically calculates parameter values from commonly available data, such as short-circuit current, open-circuit voltage, current at maximum power, etc. The model also includes an optional incidence angle modifier correlation to determine how the reflectance of the PV module surface varies with the angle of incidence of solar radiation. There are two modes for calculating the back-of-module temperature. One assumes that the cell temperature is isolated. The other assumes that cell temperature is at the outdoor air temperature, for instance, if wind is significantly cooling the module surface. The performance of an array of identical modules is assumed to be linear with the number of modules in series and parallel.

Sandia Model

The third model available in EnergyPlus for predicting the electricity generated by photovoltaics is referred to as the Sandia model and is based on research at Sandia National Laboratory (King 1996; King et al. 2003). The implementation in EnergyPlus is also based on work done by Greg Barker (2003) for the National Renewable Energy Laboratory who implemented the Sandia model as a custom type for the TRNSYS program. The model consists of a series of empirical relationships with coefficients derived from experimental tests. Once the coefficients for a specific module are available, it is a straightforward matter to use the model equations to calculate five select

points on the current-voltage curve. Although the implementation in EnergyPlus assumes that the module only operates at the maximum power point, four other points on the current-voltage curve are calculated and reported so that data are available for analyses outside of EnergyPlus. Since performance depends on cell temperature, there are two modes for predicting the back-of-module temperature. One is appropriate for most rack-mounted PV installations and calculates the cell temperature in isolation. The other mode is appropriate for building integrated applications and obtains the back-of-module temperature from the exterior surface heat balance and is discussed below. Like the equivalent one-diode model, the Sandia model predicts the performance of a single PV module. The performance of an array of identical modules is assumed to be linear with the number of modules in series and parallel. Inverter efficiency can be applied to derate the energy production. An inverter capacity forms a limit for power production from a PV system.

Building Integrated PV

All of the models described above allow PV modules to be co-located with surfaces that form the building envelope of an EnergyPlus model. The simple and Sandia PV models can also model interactions with the exterior surface heat balance through the use of a source term that accounts for energy exported in the form of electricity. The equivalent one-diode model does not currently interact with the surface heat balance. The simple model does not predict efficiency and so it has no use for the surface temperature. However, the Sandia model is tightly coupled to the surface heat balance and uses the result for exterior surface temperature as the back-of-module temperature. The coupling allows for modeling panel temperatures using all the terms of the Heat Balance Model including absorbed direct and diffuse solar radiation, net long-wave radiation with air and surroundings, convective exchange with outside air, and conduction flux in or out of the surface. Davis, et al. (2002) reported good results with similar coupling using finite difference surface conduction modeling. In EnergyPlus, conduction processes are modeled using transform methods to account for heat capacity effects in the user-defined assembly.

Limitations

EnergyPlus does not include models for inverters, charge controllers, batteries, or power-point trackers. The operation of the entire electrical system is assumed to operate in ideal ways. Modules are assumed to be always operating at the maximum power point. For a variety of reasons, actual installations of photovoltaics are often observed to exhibit system-level problems that significantly reduce electricity production. Therefore, this modeling should be considered a method of bracketing the upper end of electricity production rather than an accurate prediction of what the panels will produce in a real installation.

Validation

The EnergyPlus implementations of PV models were validated in a preliminary way by comparing results from the three models to each other and to results from an independent program (DesignPro-G v5.0). A specific type of module was selected and modeled with Chicago weather data and a latitude-tilt mounting angle. The results agreed to within 5%. The effects of coupling PV models to shading and surface heat transfer models were verified by carefully evaluating results against engineering expectations.

Solar Thermal

Flat-plate solar collectors for water heating are currently the only type of active solar thermal component in EnergyPlus. Based on the performance equations found in the ASHRAE standard (1991) and also described by Duffie and Beckman (1991), the model applies to glazed and unglazed flat-plate collectors, as well as banks of tubular (i.e., evacuated tube) collectors. A data set of commercially available solar collectors certified by the Solar Rating and Certification Corporation is provided with the program.

In EnergyPlus, solar collector modules are components that are connected to the HVAC plant loop simulation. A solar heating system for domestic hot water or space heating can be constructed using a combination of solar collectors, pumps, and water heater objects. Multiple collector modules can be combined in series and parallel using the normal EnergyPlus plant connection rules. Solar heating systems use higher-level plant managers to implement common controls, such as differential thermostats.

Currently, thermal storage for solar heating systems is accomplished with the existing EnergyPlus "simple" water heater object. Multiple tank systems with a storage tank and auxiliary water heater are not yet implemented, but they are scheduled for future releases of the program.

Validation

To validate the EnergyPlus implementation of the flat-plate solar collector, results were compared to the TRNSYS Type 1 flat-plate solar collector, which is also based on the same model equations from ASHRAE and Duffie and Beckman. The EnergyPlus model and Type 1 model were compared side-by-side by extracting and wrapping both FORTRAN subroutines with a thin layer of control code to exercise the models. Although the two models require different input variables and units, the control code made all necessary conversions. The results agreed exactly for most conditions, with the exception of very low incident angles where there were only very minor differences.

Conclusion and Future Development

Models for PV and solar thermal hot-water systems were added to the EnergyPlus whole-building energy analysis program. Implementing these models in EnergyPlus was found to be fairly straightforward and advantageous in that the models were easily expanded to account for broader set of system interactions by coupling them to the comprehensive models and algorithms that already existed for solar radiation, surface shading and reflections, dynamic surface heat transfer, and HVAC system components.

Further development of both PV and solar thermal components in EnergyPlus is scheduled for future releases. PV developments will include electrical loops and system models to account for the effects of inverters, batteries, etc. Solar thermal developments will include integrated collector storage (ICS) modules, concentrating collectors, and enhancements to the basic flat-plate model, as well as more thermal storage capabilities in the EnergyPlus plant system such as multiple storage tanks. Hybrid PV and thermal system models and unglazed transpired collectors are also planned.

References

- ASHRAE. 1991. ASHRAE Standard 93-1986 (RA 91): Methods of Testing to Determine the Thermal Performance of Solar Collectors. Atlanta: American Society of Heating, Refrigerating and Air-Conditioning Engineers, Inc.
- Barker, G. 2003. Predicting Long-Term Performance of Photovoltaic Arrays. Submitted as deliverable for NREL subcontract LAX-1-30480-02. Currently in DRAFT
- Crawley, D.B., L.K. Lawrie, F.C. Winkelmann, W.F. Buhl, Y.J. Huang, C.O. Pedersen, R.K. Strand, R.J. Liesen, D.E. Fisher, M.J. Witte, and J. Glazer. 2001. "EnergyPlus: Creating a New-Generation Building Energy Simulation Program", *Energy and Buildings* 33, 319-331 (2001).
- Davis, M.W., Fannery, A.H., and Dougherty B.P. 2002. Measured Versus Predicted Performance of Building Integrated Photovoltaics. Solar 2002 Conference, Sunrise on the Reliable Energy Economy. June 15-19, 2002, Reno, NV.
- Duffie, J. A., and Beckman, W. A. 1991. *Solar Engineering of Thermal Processes*, Second Edition. New York: Wiley-Interscience.
- Eckstein, Jürgen Helmut. Detailed Modeling of Photovoltaic Components. M. S. Thesis - Solar Energy Laboratory, University of Wisconsin, Madison: 1990.
- Groth, C.C., and Lokmanhekim, M. 1969. Shadow – A New Technique for the Calculation of Shadow Shapes and Areas by Digital Computer. Second Hawaii International Conference on System Sciences. Honolulu, HI, Jan. 22-24, 1969.
- King, D.L. 1996. Photovoltaic Module and Array Performance Characterization Methods for All System Operating Conditions. Sandia National Laboratory. Albuquerque, NM 87185
- King, D.L., Boyson, W.E., Kratochvil J.A. 2003. Photovoltaic Array Performance Model. Sandia National Laboratories, Albuquerque, NM 87185, November 2003 currently in DRAFT
- Perez, R., P. Ineichen, R. Seals, J. Michalsky, and R. Stewart. 1990. "Modeling Daylight Availability and Irradiance Components from Direct and Global Irradiance", *Solar Energy* 44, 271-289 (1990).
- UIUC, LBNL. 2004. EnergyPlus Engineering Document: The Reference to EnergyPlus Calculations, U.S. Department of Energy, 2004.
- Ulleberg, Øystein. HYDROGEMS Component Library for TRNSYS 15 User Manual, Institute for Energy Technology, Kjeller, Norway.
- Walton, G.N. 1983. The Thermal Analysis Research Program Reference Manual. National Bureau of Standards. (now NIST) February 1983.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to Department of Defense, Executive Services and Communications Directorate (0704-0188). Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ORGANIZATION.

1. REPORT DATE (DD-MM-YYYY) July 2004		2. REPORT TYPE Conference Paper		3. DATES COVERED (From - To)		
4. TITLE AND SUBTITLE Photovoltaic and Solar Thermal Modeling with the EnergyPlus Calculation Engine: Preprint			5a. CONTRACT NUMBER DE-AC36-99-GO10337			
			5b. GRANT NUMBER			
			5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S) B.T. Griffith and P.G. Ellis			5d. PROJECT NUMBER NREL/CP-550-36275			
			5e. TASK NUMBER BEC3.1001			
			5f. WORK UNIT NUMBER			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) National Renewable Energy Laboratory 1617 Cole Blvd. Golden, CO 80401-3393				8. PERFORMING ORGANIZATION REPORT NUMBER NREL/CP-550-36275		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S) NREL		
				11. SPONSORING/MONITORING AGENCY REPORT NUMBER		
12. DISTRIBUTION AVAILABILITY STATEMENT National Technical Information Service U.S. Department of Commerce 5285 Port Royal Road Springfield, VA 22161						
13. SUPPLEMENTARY NOTES						
14. ABSTRACT (Maximum 200 Words) EnergyPlus is a whole-building energy analysis software program developed by DOE. It was recently expanded with the addition of new active solar components for simulation of photovoltaic and solar thermal hot-water heating systems. The active solar models were integrated into the program because low- or zero-energy buildings often use renewable energy resources to accomplish their energy-saving goals. This paper provides an overview of the new models for PV and solar collectors in EnergyPlus and describes some preliminary efforts to validate the implementations.						
15. SUBJECT TERMS EnergyPlus; High-Performance Buildings; energy analysis software; energy simulation software; energy simulation; commercial buildings						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT UL	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (Include area code)	